V.3.3-SNOW-17 HYDRO-17 SNOW MODEL OPERATION

Bookmarks

Identifier	•	•	•		•				•		•	•	•		•	•	•	•	[<u>Bookmark</u>]
Application																			[<u>Bookmark</u>]
Description																			[Bookmark]
References																			[Bookmark]
Allowable Dat	ta	T:	ime	9	In	te	rv	al	S										[<u>Bookmark</u>]
Time Series	Js	ed																	[<u>Bookmark</u>]
Input Summary	У																		[<u>Bookmark</u>]
Sample Input	a	nd	Οι	ıt:	pu	t													[<u>Bookmark</u>]
Execution Ro	ıt.	ine	e J	Pr	in	t	Ou	tp	ut										[<u>Bookmark</u>]
Error and Wa:	rn.	in	g N	Ме	SS	ag	es												[<u>Bookmark</u>]
Carryover Tra	an	sf	er	R	ul	es													[<u>Bookmark</u>]
Card Punch La	im.	ita	at:	io	ns														[<u>Bookmark</u>]
Figures																			[<u>Bookmark</u>]
[Bottom]																			

Contents

																		_	age
Identifier		•				•	•	•	•	•	•	•	•	•	•	•	•		<u>1</u>
Application							•	•	•	•	•	•	•	•	•	•	•		<u>1</u>
Description						•	•			•									<u>1</u>
References																			3
Allowable Data Ti	.me	Int	ter	va	ls														3
Time Series Used																			3
Input Summary .																			4
Sample Input and	Out	.put	t																$1\overline{1}$
Error and Warning																			
Carryover Transfe			_																
Card Punch Limita																			

 $[\underline{Next}]$ [Previous] $[\underline{Bookmarks}]$ $[\underline{Top}]$

Identifier: SNOW-17

[Next] [Previous] [Bookmarks] [Top]

Application: All programs

[Next] [Previous] [Bookmarks] [Top]

<u>Description</u>: This Operation is the snow accumulation and ablation model first described in HYDRO-17 [Anderson (1973)]. This model uses air temperature as the only index to energy exchange at the snow-air interface.

A complete description of the model is in Chapter II.2-SNOW-17 [Hyperlink].

The original HYDRO-17 model was programmed to use data and perform computations on a 6 hour data time interval. This Operation is

Page

programmed so that the data time interval is variable. The computational time interval (i.e., the minimum period for which the Operation can be executed) is the data time interval of the air temperature data. Precipitation data can be supplied more frequently. Rain+melt is calculated for the same time interval used for precipitation. More frequent computation of rain plus melt allows for simulating the response of high intensity rain on small headwater basins without having to supply temperature data at the same frequency. Observed data values for use in making updates or comparisons can be supplied at any multiple of the computational time interval.

The original HYDRO-17 model used a sinusoidal seasonal melt-factor variation when computing melt during non-rain periods. An alternative variation was later added for use in Alaska. This Operation also allows for a user specified seasonal melt-factor variation. This option was partly added for use in watersheds where glaciers have a major contribution to the amount of meltwater.

The original HYDRO-17 model used air temperature to determine whether precipitation was in the form of rain or snow. This Operation has 3 ways to determine the form of the precipitation. The 3 methods, in their order of precedence, are as follows:

- 1. The percent of precipitation that is rain and snow can be specified directly for each data time interval. This is done by using a percent snowfall time series or by specifying the form of precipitation at run time when making operational forecasts.
- 2. The elevation that separates rain from snow can be input to the Operation for each data time interval. In this case the area-elevation curve must be specified so that the percent of the area receiving rain and the percent receiving snow can be computed. The rain-snow elevation can be generated by using the Rain-Snow Elevation Operation (see V.3.3-RSNWELEV [Hyperlink]).
- 3. Air temperature is used to determine the form of precipitation. If the temperature is greater than a threshold value (the PXTEMP parameter), the precipitation is rain, otherwise it is snow. This is the default method used when the other methods are not enabled or when the percent snowfall time series contains missing values.

The Operation contains procedures for updating water-equivalent and areal extent of snow cover in both operational and calibration applications. Some features of the updating procedures are:

- 1. The updating procedures can be turned 'on' or 'off' at run time by the user. When the update option is 'on', updating takes place only when observed data are available and the difference between computed and observed values exceeds a specified tolerance.
- 2. Observed data are always supplied in time series form in the Calibration System programs. In the Operational Forecast System

programs observed data can be supplied in time series form or directly at run time. Time series are generally used when data are observed frequently and/or automatically processed. Direct entry is useful for infrequent or manually processed observations.

3. When updating water-equivalent, the areal extent of the snow cover is automatically adjusted when the water-equivalent is updated. This adjustment is based on the relationship described by the areal depletion curve.

The Operation also includes a melt correction factor that can be used to increase or decrease melt during non-rain periods. This factor is supplied at run time.

[Next] [Previous] [Bookmarks] [Top]

References:

04/21/2005

Anderson, Eric A., 1973, National Weather Service River Forecast System - Snow Accumulation and Ablation Model, NOAA Technical Memorandum NWS HYDRO-17, U.S. Dept. of Commerce, Silver Spring, MD.

[Next] [Previous] [Bookmarks] [Top]

Allowable Data Time Intervals: 1, 2, 3, 4, 6, 8, 12 and 24 hours

[Next] [Previous] [Bookmarks] [Top]

rfs:533snow17.wpd

Time Series Used: Time series used in this Operation are as follows:

General Type	<u>Dimn</u>	<u>Units</u>	<u>Use</u>	Required	Form of Output T.S.	Data Time <u>Interva</u> l	Missing Values <u>Allowed</u>
Precipitation	L	MM	I	yes	n/a	any	no
Air temperature	TEMP	DEGC	I	yes	n/a	any <u>1</u> /	no
Rain+melt	L	MM	0	no	replaces	any <u>2</u> /	no
Percent snowfall	DLES	PCTD	I	no	n/a	any <u>2</u> /	yes
Rain-snow elevation	L	М	I	no	n/a	any <u>3</u> /	no
Observed water- equivalent	L	MM	I	no	n/a	any <u>4</u> /	yes
Simulated water- equivalent	L	MM	0	no	replaces	any <u>4</u> /	no
Observed areal cover	DLES	PCTD	Ι	no	n/a	any <u>4</u> /	yes
Simulated areal	DLES	PCTD	0	no	replaces	any <u>4</u> /	no

V.3.3-SNOW-17-3

General Type	<u>Dimn</u>	<u>Units</u>	<u>Use</u>	Required	Form of Output T.S.	Data Time <u>Interva</u> l	Missing Values <u>Allowed</u>
cover							
Simulated snow depth	L	CM	0	no	replaces	any <u>4</u> /	no
Observed snow depth	L	CM	I	no	replaces	any <u>4</u> /	no

- $\underline{1}/$ Must be an even multiple of the data time interval for precipitation data.
- $\underline{2}/$ Must be the same as the data time interval for precipitation data.
- $\underline{3}/$ Must be the same as the data time interval for temperature data.
- $\underline{4}/$ Must be an even multiple of the data time interval for air temperature data.

[Next] [Previous] [Bookmarks] [Top]

Input Summary: The card input for this Operation is as follows:

Card	<u>Format</u>	Columns	<u>Contents</u>
1	5A4	1-20	Header information (e.g. name of the area or point)
	F5.0	21-25	Elevation of the area or point (units of \mathbf{M})
	F5.0	26-30	Latitude of the area or point in degrees; if greater than or equal to 54.0 then the Alaskan seasonal melt-factor variation is used
	1XA4	32-35	Printer output control; enter 'ALL' for output on all days; enter 'NONE' for no output; default is output on last day of observed data, last day of run period and days when: o snow first appears o snow disappears o snowfall or rain-on-snow exceeds 5 MM o surface energy exchange exceeds 5 MM o observed data are available
	2X,A3	38-40	Observed time series indicator; default is no observed time series used; enter 'YES' if observed water-equivalent or

<u>Card</u>	<u>Format</u>	<u>Columns</u>	<u>Contents</u>
			areal snow cover time series are used
	2X,A3	43-45	Simulated time series indicator; default is no simulated time series produced; enter 'YES' if the Operation should generate simulated water-equivalent or areal snow cover time series
	1X,A4	47-50	Option to store sums of snow cover water balance variables; default is sums not stored; enter 'SUMS' to store water balance variables
	4X,A4,A2	55-60	Update option (only used for Calibration System programs); default is no updating; enter 'UPDATE' to update water-equivalent and areal snow cover when observed values are available
	1X,A4	62-65	Read carryover option; default is to set carryover values to indicate no snow cover exists; enter 'RDCO' to input initial snow conditions
	1X,A4	67-70	Rain-snow elevation option; default is to not use rain-snow elevation data; enter 'AVSE' to use an areal versus elevation curve and a rain-snow elevation time series to determine the form of precipitation
2	3X , I2	4-5	Data time interval in hours for precipitation, rain plus melt and percent snowfall time series; default is 6
	2X,2A4	8-15	Identifier of precipitation time series
	1X,A4	17-20	Data type code of precipitation time series
	F10.0	21-30	PXADJ; precipitation adjustment factor; applied to all precipitation
	7X,2A4	38-45	Identifier of rain plus melt time series; blank if not used
	1X,A4	47-50	Data type code of rain plus melt time series; blank if not used
	7X , 2A4	58-65	Identifier of percent snowfall time

<u>Card</u>	<u>Format</u>	<u>Columns</u>	<u>Contents</u>
			series; blank if not used
	1X,A4	67-70	Data type code of percent snowfall time series; blank if not used
3	2X,2A4	3-10	Identifier of air temperature time series
	1X,A4	12-15	Data type code of air temperature time series
	3X,I2	19-20	Data time interval in hours of air temperature time series; must be a multiple of the data time interval of the precipitation time series; default is 6
	F10.0	21-30	Elevation associated with the air temperature time series in meters; default is elevation associated with temperature data is the same as the elevation of the area or point

Lapse rates only needed if the elevation of the temperature data differs from the elevation of the area or point where the model is being applied.

F5.0	31-35	Lapse rate at time of maximum temperature (assumed to occur at 3 PM local standard time; units of DEGC/100M)
F5.0	36-40	Lapse rate at time of minimum temperature (assumed to occur at 6 AM local standard time; units of DEGC/100M)

Card 3A only included if the rain-snow elevation option on card 1 is set to 'AVSE'.

3A	3X , I2	4-5	Number of points used to define the area-elevation curve; maximum is 12; does not include the maximum and minimum elevation points
	F10.0	6-15	Minimum elevation (units of FT or M)
	F10.0	16-25	Maximum elevation (units of FT or M)
	1X,A4	27-30	<pre>Elevation units for cards 3A and 3B: 'ENGL' = English units (units of</pre>

Card	<u>Format</u>	<u>Columns</u>	<u>Contents</u>
	2X,2A4	33-40	Identifier of the rain-snow elevation time series
	1X,A4	42-45	Data type code of rain-snow elevation time series

Card 3B included if the number of points used to define the areaelevation curve on card 3A is greater than zero. Card 3B can contain up to 4 points. Card 3B is repeated as necessary to input all points. Elevations must be in an increasing order.

3B	F10.0	1-10	Elevation of the 1st point on area- elevation curve (units of FT or M)
	2X,F3.2	13-15	Decimal fraction of area below the 1st elevation point
	F10.0,2X,F3.2	16-30	Second pair of elevation and fraction of area below points (if needed)
	F10.0,2X,F3.2	31-45	Third pair of points (if needed)
	F10.0,2X,F3.2	46-60	Fourth pair of points (if needed)

Card 4 only included if the observed time series indicator on Card 1 is set to 'YES'.

4	2X,2A4	3-10	Identifier of observed water-equivalent time series; blank if not used
	1X,A4	12-15	Data type code for observed water- equivalent time series; blank if not used
	3X,I2	19-20	Data time interval of observed water- equivalent time series; must be a multiple of the data time interval of the temperature time series; blank if not used
	12 , 2A4	33-40	Identifier of observed areal extent of snow cover time series; blank if not used
	1X,A4	42-45	Data type code of observed areal snow cover time series; blank if not used
	3X,I2	49-50	Data time interval of observed areal snow cover time series; must be a multiple of the data time interval of the temperature time series; blank if not used

<u>Card</u>	<u>Format</u>	Columns	<u>Contents</u>
	2X,2A4	53-60	Internal identifier for the observed snow depth time series; blank if none used
	1X,A4	62-65	Data type code for the observed snow depth time series; blank if none used
	3X , I2	69-70	Data time interval for the observed snow depth time series; blank if none used
	only inclu is set to		e simulated time series indicator on
5	2X,2A4	3-10	Identifier of simulated water- equivalent time series; blank if not used
	1X,A4	12-15	Data type code of simulated water- equivalent time series
	3X , I2	19-20	Data time interval of simulated water- equivalent time series; must be a multiple of the data time interval of the temperature time series; blank if not used
	12X,2A4	33-40	Identifier of simulated areal extent of snow cover time series; blank if not used
	1X,A4	42-45	Data type code of simulated areal snow cover time series; blank if not used
	3X,I2	49-50	Data time interval of simulated areal snow cover time series; must be a multiple of the data time interval of the temperature time series; blank if not used
	2X,2A4	53-60	Internal identifier for the simulated snow depth time series; blank if none used
	1X,A4	62-65	Data type code for the simulated snow depth time series; blank if none used
	3X , I2	69-70	Data time interval for the simulated snow depth time series; blank if none used

Card 6 contains the major parameters for the snow model.

Card	<u>Format</u>	Columns	<u>Contents</u>						
6	F5.0	1-5	SCF (snowfall correction factor)						
	F5.0	6-10	MFMAX (maximum non-rain melt factor; units of MM/DEGC/6HR)						
	F5.0	11-15	MFMIN (minimum non-rain melt factor; units of MM/DEGC/6HR)						
	F5.0	16-20	UADJ (average value of the wind function during rain-on-snow events; units of MM/MB)						
	F5.0 21-25 SI (areal water-equivalent a there is always 100 percent units of MM)								
	4X,I1	30	Seasonal melt-factor variation indicator: 0 = use normal seasonal melt-factor variation (curve used is based on latitude) 1 = use user specified seasonal melt-factor variation						
Card 6A is only needed if			column 30 card 6 equals 1.						
6A	12F5.0	1-60	Seasonal melt-factor variation (specified as decimal fraction of where the melt-factor lies between MFMIN and MFMAX on the 16th of each month; i.e. 0.0 = MFMIN, 1.0 = MFMAX, 0.5 = ((MFMIN+MFMAX)*0.5); this option is primarily intended for use in calculating melt from glaciers						
Card 7 paramet		minor para	meters for the snow model and updating						
7	F5.0	1-5	NMF (maximum negative melt factor; units of MM/DEGC/6HR)						
	F5.0	6-10	TIPM (antecedent snow temperature index parameter; range is 0.1 to 1.0)						
	F5.0	11-15	MBASE (base temperature for non-rain melt factor; units of DEGC)						
	F5.0	16-20	PXTEMP (temperature that separates rain from snow; units of DEGC; rain if temperature is greater than PXTEMP; snow if less than or equal to PXTEMP; not used if a valid percent snowfall time series value is available or if						

<u>Card</u>	<u>Format</u>	<u>Columns</u>	<u>Contents</u>
			rain-snow elevation option is selected)
	F5.0	21-25	PLWHC (maximum amount of liquid-water held against gravity drainage-decimal fraction)
	F5.0	26-30	DAYGM (daily melt at the snow-soil interface; units of MM)
System	programs a	nd are on	ys needed for Operational Forecast ly needed for Calibration System ion on Card 1 is turned on.
	F5.0	31-35	Tolerance used when updating water- equivalent-decimal fraction; updating only occurs if Simulated-Observed is greater than tolerance times Observed
	F5.0	36-40	Tolerance used when updating areal extent of snow cover; decimal fraction; updating only occurs if Simulated-Observed is greater than the tolerance
8	9F5.0	1-45	Areal depletion curve; decimal fraction; areal snow cover at WE/Ai ratios of 0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8 and 0.9; for WE/Ai = 0.0, areal cover = 0.05; for WE/Ai = 1.0, areal cover = 1.0
Card 9 'RDCO'	only needed	d if read	carryover option on Card 1 is set to
9	F5.0	1-5	Initial water-equivalent of solid (ice) portion of the snow cover (units of MM)
	F5.0	6-10	Initial heat deficit (units of MM)
	F5.0	11-15	Initial amount of liquid-water held against gravity drainage (units of MM)
	F5.0	16-20	TINDEX (initial antecedent snow temperature index; units of DEGC)
	F5.0	21-25	ACCMAX (maximum water-equivalent that has occurred since snow began to accumulate (units of MM)
	4X,I1	30	Read remaining carryover option; default is do not input remaining carryover values and calculate them based on card 9 values: 1 = read remaining carryover values

<u>Card</u>	<u>Format</u>	Columns	<u>Contents</u>
	F5.0	31-35	<pre>SNDPT (snow depth; units of CM); blank if none used</pre>
	F5.0	36-40	<pre>SNTMP (average snow cover temperature; units of DEGC); blank if none used</pre>

Card 10 only needed if the option to read the remaining carryover values is set to 1 on card 9.

10	F5.0	1-5	SB (units of MM)
	F5.0	6-10	SBAESC (units of decimal fraction)
	F5.0	11-15	SBWS (units of MM)
	F5.0	16-20	STORGE (units of MM)
	F5.0	21-25	AEADJ (units of MM)
	7F5.0	26-60	Lagged excess water (units of MM); number of values is 5/timeint+2 where timeint is the precipitation data time interval

[Next] [Previous] [Bookmarks] [Top]

Sample Input and Output: Sample input is shown in Figure 1 [Bookmark]. Sample output from the parameter print routine is shown in Figure 2 [Bookmark]. Sample output from the execution routine is shown in Figure 3 [Bookmark].

[Next] [Previous] [Bookmarks] [Top]

<u>Error and Warning Messages</u>: The error and warning messages generated by this Operation and the corrective action to take when they occur are as follows:

- A. Messages that can occur during setup:
 - 1. **ERROR** TIME INTERVAL (XX HOURS) OF THE TEMPERATURE DATA IS NOT A MULTIPLE OF THE TIME INTERVAL (XX HOURS) OF THE PRECIPITATION.

Action: Change one or the other data time interval so the data time interval of the temperature data is a multiple of that for precipitation.

2. **WARNING** AT LEAST ONE OF THE LAPSE RATES ARE NOT POSITIVE. CHECK THAT VALUES ARE CORRECT.

Action: Temperature normally decreases with elevation, though in a few areas inversion conditions predominate, especially for minimum temperatures, during the snow season.

3. **ERROR** THE TIME INTERVAL OF A TIME SERIES (I.D.=XXXXXXXX TYPE=XXXX XX HOURS) IS NOT A MULTIPLE OF THE TIME INTERVAL (XX HOURS) OF THE TEMPERATURE DATA.

Action: Change data time intervals so the data time interval is a multiple of that for the temperature data.

4. **ERROR** ONE OR MORE VALUES OF THE AREAL DEPLETION CURVE ARE LESS THAN THE PRECEDING VALUE.

Action: Make sure each value of the areal depletion is greater than or equal to the preceding value.

5. **ERROR** THE NUMBER OF AREA-ELEVATION CURVE POINTS INPUT (XX) EXCEEDS 12.

Action: Reduce the number of points used to define the areaelevation curve.

6. **ERROR** ONE OR MORE VALUES IN THE AREA-ELEVATION CURVE ARE LESS THAN THE PRECEDING VALUE.

Action: Make sure that the elevations and fraction of area below each elevation are in increasing order.

- B. Messages that occur during execution.
 - 1. **WARNING** SNOW BALANCE RESIDUAL EXCEEDS 1 mm. RESIDUAL = XXXX.XX.

Action: Operation is not executing properly, call for assistance.

[Next] [Previous] [Bookmarks] [Top]

<u>Carryover Transfer Rules</u>: The following adjustments are applied to carryover values when parameters are changed:

- 1. Liquid-water held against gravity drainage is reduced by the amount that it exceeds PLWHC multiplied by the ice portion of the snow cover.
- 2. SB and SBWS are decreased by the same amount that liquid-water is reduced.
- 3. SBAESC is recomputed if SI or the areal depletion curve are changed.
- 4. Lagged excess water is redistributed if the data time interval of the precipitation data is changed. If the data time interval is decreased, some of the excess water is lost.

All other carryover values are not affected by changes to parameters.

[Next] [Previous] [Bookmarks] [Top]

<u>Card Punch Limitations</u>: The punched card formats for this Operation are as follows. No checks are made to determine if values exceed the specified range since this should seldom occur.

Parameters or Variables	Punch <u>Format</u>	Maximum Value	Minimum <u>Value</u>
PXADJ	F10.3	999999.999	0.001
Elevation of temperature data, elevations in area-elevation curve	F10.0	999999999.	-99999999.
Lapse rates	F5.2	99.99	-9.99
Elevation of area, SI, LIQW	F5.0	9999.	0.0 (Elev.=-999.)
Latitude, MBASE, PXTEMP, NEGHS, TINDEX, STORAGE, Lagged excess water	F5.1	999.9	0.0 (Temp.=-99.9)
MFMAX, MFMIN, SCF, NMF, TIPM, DAYGM,	F5.2	99.99	0.0
UADJ	F5.3	9.999	0.0
WE, ACCMAX, SB, SBWS, AEADJ	I5	99999	0
User specified seasonal melt-factor variation, depletion curve, SBAESC, PLWHC, updating tolerances	F5.2	1.00	0.0
Fraction of area below specified elevation	F3.2	.99	.01

[Back] [Next] [Previous] [Bookmarks] [Top]

Figure 1. Sample card input for Operation SNOW-17

		-	Column -							
5 10 15 20	25 30	35	40 45	50	55	60	65	70	75	80
+	+	+	+		+-	+-	+	+-	+	+
SNOW-17 AFTNC										
PECATONICA AFTON	305. 41.7	ALL	YES	5			RDCO			
6 AFTNC MAP	1.000		AFTNC	RAIM						
AFTNC MAT	5									
AFTNC SWE 2	_			0						
1.0 1.8 0.6 .10	75.									
0.20 0.20 0.0 0.	.15 0.00	0.00	0.10							
0.15 0.30 0.50 0.6	1 0.75 0.82	0.88	0.92 0.96							
106. 10. 217.	130									

[Back] [Next] [Previous] [Bookmarks] [Top]

Figure 2. Sample output from Operation SNOW-17 print parameter routine

****** SNOW-17 OPERATION NAME=AFTNC PREVIOUS NAME= ****** SNOW MODEL OPERATION FOR PECATONICA AFTON ELEV= 305. M LAT.= 41.7 COMPUTATIONAL TIME INTERVAL IS 6 HOURS. TIME SERIES USED BY THIS OPERATION. CONTENTS TYPE TIME INTERVAL I.D. OTHER o HOURS PXADJ= 1.00 6 HOURS TAELEV= 305. 6 HOURS MAP MAT PRECIPITATION AFTNC AIR TEMPERATURE AFTNC RAIM 6 HOURS
24 HOURS AFTNC RATN+MELT SIMULATED W.E. AFTNC SNOW COVER VARIABLES DISPLAYED EVERY DAY. PARAMETER VALUES MAJOR PARAMETERS SCF MFMAX MFMIN UADJ 1.00 1.80 0.60 0.100 75. MINOR PARAMETERS NMF TIPM MBASE PXTEMP PLWHC DAYGM 0.20 0.20 0.0 0.6 0.15 0.00 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0 0.05 0.15 0.30 0.50 0.64 0.75 0.82 0.88 0.92 0.96 1.0 DEPLETION CURVE WE/AI COVER UPDATING PARAMETERS TOLERANCES W.E. COVER 0.00 0.10 SNOW COVER CONDITIONS FOR PECATONICA AFTON

WE NEGHS LIQW TINDEX ACCMAX 106. 10.0 15.9 -7.0 130.

[Back] [Next] [Previous] [Bookmarks] [Top]

Figure 3. Sample output from Operation SNOW-17 execution routine

'AFTNC	' SNOW-17 OUTPUT FOR PECATONICA AFTON DAILY OUTPUT IS FOR HOUR 5 TIME ZONE=MST				3/1993 r	(UNITS	ARE 'IN' EX	CEPT FOR A		
DAY	SNOWFALL	RAIN ON SNOW	ENERGY EXCHANGE	SIM. AREAL COVER	PCT. LIQ. WATER	HEAT DEFICIT	SIM. WE	OBS. WE	OBS. COVER	RAIN-SNOW
								ODS. WE	ODS. COVER	ELEVALION
30	0.00	0.00	0.10	1.00	15.0	0.29	4.80			
31	0.00	0.00	0.23	1.00	15.0	0.06	4.80			
1	0.00	0.00	0.44	1.00	15.0	0.00	4.44			
2	0.00	0.00	0.86	1.00	15.0	0.00	3.48			
3	0.00	0.00	0.96	0.91	15.0	0.00	2.38			
4	0.00	0.00	0.83	0.70	15.0	0.00	1.38			
5	0.00	0.00	0.47	0.43	15.0	0.00	0.81			

[Back] [Next] [Previous] [Bookmarks] [Top]